

HUVIRON

Create your own safety

F-RN1109



KEY FEATURES

- IP Camera Input: 9CH
- Compression Method: H.265/H.265+/H.264+/H.264
- Recording Resolution: 4K/5M/4M/3M/1080P/960P/720p
- 1 HDD, Up to 8TB

	MODEL	F-RN1109
System	Main Processor	ARM Cortex A7
	Operating System	Embedded LINUX
Video	Input	9CH 2592 x 1944, 2560x1440, 2048 x 1536, 1920 x1080, 1280 x 960, 1280 x 720)
	Output	1VGA, 1HD
Audio	Input	/
	Output	1 jack headphone 3.5mm
	Audio Bit Rate	64Kbps
	Audio Compression standard	G711u, G711a, G726
Alarm	Sensor Input	/
	Output	/
	Motion Detection	9 Channel
	Trigger Events	Recording, Email, FTP, Snapshot, Buzzer and Screen Tips
Display	HD Output1	1920x1080/1280x1024/1280x720/60Hz
	HD Output2	/
	VGA	1920x1080/1280x1024/1280x720/60hz
	Display Split	9/8/4CHxD1 1CHx1080P/3MP/4MP/5MP
	Digital Zoom	YES
Recording	OSD	Camera Title, Time, Recording, Motion Detection, Event Alarm
	Video Compression	H265/H264/H265+/H264+
	Resolution	5MP(2592x1944), 4MP(2688x1520/2560x1440), 3MP(2048x1536), 1080P(1920x1080), 960P(1280x720), D1(720x576/720x480)
	Record Rate	PAL :5MP@9x25fp,4MP@9x25fp,3MP@9x25fp, 1080P@9x25fp, 960P@9x25fp, 720P@9x25fp, D1@9x25fp NTSC: 5MP@9x30fp,4MP@9x30fp,3MP@9x30fp, 1080P@9x30fp, 960P@9x30fp, 720P@9x30fp, D1@9x30fp
Record Mode	Manual/Timer/Motion Detection	

Playback & Backup	Local Sync Playback	1CH 4M@30fps/5MP@30fps 2CH 3M@30fps 4CH 1080P@30fps/ 960P@30fps/720P@30fps
	Remote Sync Playback	YES
	Search Mode	ALL, Channel, Manual, Time, Date, Motion Detection, Event Alarm
	Playback Functions	Play, Pause, Stop, Rewind, Fast play, Slow Play, Full Screen, Frame Play ,Frame Rewind, Digital Zoom
Network	Backup Mode	USB Device/Network
	Interface	1RJ45 10M/100M
	Incoming Bandwidth	60MB
	Outgoing Bandwidth	/
	Network Functions	TCP/IP,HTTP,UpnP, DNS, NTP, SMTP, PPPoE, DHCP, FTP, DDNS, RTP, RTSP, RTCP, p2p
	Onvif Version	Support Onvif 2.8
	Cloud Support (P2P)	Yes
	Smart Phone	iPhone, iPad, Android, Android Pad
	POE	/
	WIFI	/
Storage	Interface Type	1 SATA Hard Disk Interface
	Capacity	Up to 8TB capacity
	eSATA	/
General	Language	English, Vietnamese
	USB Interface	2 USB 2.0 Interfaces
	RS485	/
	Power Supply	DC12V/2A
	Working Environment	-10~55°C/ 10~90%
	Dimension (WxDxH)	260 x 215 x 43 mm
Weight	2KG (without HDD)	