

F-RN8264LE



KEY FEATURES

- IP Camera Input: 64CH
- Compression Method: H.265/H.265+/H.264+/H.264
- Recording Resolution: 4K/5M/4M/3M/1080P/960P/720P
- Two output HDMI
- 8 HDD Up to 48TB, 1eSATA
- Support 4K Display Resolution

	MODEL	F-RN8264LE
System	Main Processor	ARM Cortex A7
	Operating System	Embedded LINUX
Video	Input	64CH
	Output	1VGA, 2HD
Audio	Input	/
	Output	1 jack 3.5mm
	Audio Bit Rate	64Kbps
	Audio Compression standard	G711u, G711a
Alarm	Sensor Input	16
	Output	4
	Motion Detection	64 Channel
	Trigger Events	Recording, Email, FTP, Snapshot, Buzzer and Screen Tips
Display	HD Output1	4k(4096x2160),5MP(2592x1944), 4MP(2688x1520/2560x1440),3MP(2048x1536), 1080P(1920x1080),960P(1280x960), 720P(1280x720),D1 (720x576/720x480)
	HD Output2	(1920 x 1080, 1280 x 1024, 1280 x 720, 1024 x 768) /60Hz
	VGA	(1920 x 1080, 1280 x 1024, 1280 x 720, 1024 x 768) /60Hz
	Display Split	64CHxD1/36CHxD1/25CHxD1/16CHxD1/9CHxD1/ 4CHxD1/1CHx1080P/1CHx3MP/1CHx4MP/ 1CHx5MP/1CHx4k
	Digital Zoom	YES
	OSD	Camera Title, Time, Recording, Motion Detection, Event Alarm
Recording	Video Compression	H265/H264/H265+/H264+
	Resolution	4k(4096x2160),5MP(2592x1944), 4MP(2688x1520/2560x1440),3MP(2048x1536), 1080P(1920x1080),960P(1280x960), 720P(1280x720),D1 (720x576/720x480)
	Record Rate	PAL :12MP@29x25fp,4k@35x25fp,5MP@58x25fp, 4MP@64x25fp,3MP@64x25fp,1080P@64x25fp, 960P@64x25fp,720P@64x25fp, D1@64x25fp NTSC: 12MP@29x30fp,4k@35x30fp, 5MP@58x30fp,4MP@64x30fp,3MP@64x30fp, 1080P@64x30fp, 960P@64x30fp, 720P@64x30fp, D1@64x30fp
	Record Mode	Manual\Timer\Motion Detection

Playback & Backup	Local Sync Playback	4CH 4K@30fps, 6CH 5MP@30fps, 8CH 4MP@30fps, 10CH 3M@30fps, 16CH 1080P@30fps, 16CH 960P@30fps, 16CH 720P@30fps
	Remote Sync Playback	YES
	Search Mode	ALL, Channel, Manual, Time, Date, Motion Detection, Event Alarm
	Playback Functions	Play, Pause, Stop, Rewind, Fast play, Slow Play, Full Screen, Frame Play ,Frame Rewind, Digital Zoom
	Backup Mode	USB Device/Network
Network	Interface	2 RJ45 10M/100M/1000M
	Incoming Bandwidth	350MB
	Outgoing Bandwidth	/
	Network Functions	TCP/IP,HTTP,UpnP, DNS, NTP, SMTP, PPPoE, DHCP, FTP, DDNS, RTP, RTSP, RTCP, p2p
	Onvif Version	Support Onvif 2.8
	Cloud Support (P2P)	Yes
	Smart Phone	iPhone, iPad, Android, Android Pad
Storage	POE	/
	WIFI	/
	Interface Type	8 SATA Hard Disk Interface (3.5" SATA)
	Capacity	Up to 48TB capacity
General	eSATA	1 eSATA interface
	Language	English, Vietnamese
	USB Interface	2 USB 2.0 Interfaces ,1 USB 3.0 Interface
	RS485	1 Port, for PTZ Control
	Power Supply	100 to 240 VAC, 50 to 60 Hz
	Working Environment	-10~55°C/ 10~90%
Dimension (WxDxH)	2U, 440 x 450 x 95 mm	
Weight	3,5KG (without HDD)	