

## F-RNP1108

HUVIRON

### KEY FEATURES

- IP Camera Input: 9CH
- H.265+/H.265/H.264+/H.264
- 8 port PoE 100Mbps, Support Plug and Play
- 1 HDD, Up to 8TB

	MODEL	F-RNP1108
System	Main Processor	ARM Cortex A7
	Operating System	Embedded LINUX
Video	Input	9CH 2592 x 1944, 2560x1440, 2048 x 1536, 1920 x1080, 1280 x 960, 1280 x 720)
	Output	1VGA, 1HD
Audio	Input	/
	Output	1 jack 3.5mm Headphone
	Audio Bit Rate	64Kbps
	Audio Compression standard	G711u, G711a, ADPCM_DV14
Alarm	Sensor Input	/
	Output	/
	Motion Detection	9 Channel
	Trigger Events	Recording, Email, FTP, Snapshot, Buzzer and Screen Tips
Display	HD Output1	(1920x1080/1280x1024/1280x720)/60Hz
	HD Output2	/
	VGA	(1920x1080/1280x1024/1280x720)/60Hz
	Display Split	9/8/4 kênh xD1 1 Kênh x1080P/3MP/4MP/5MP
	Digital Zoom	YES
	OSD	Camera Title, Time, Recording, Motion Detection, Event Alarm
Recording	Video Compression	H265/H264/H265+/H264+
	Resolution	5MP(2592x1944), 4MP(2688x1520/2560x1440), 3MP(2048x1536), 1080P(1920x1080), 960P(1280x960), 720P(1280x720), D1(720x576/720x480)
	Record Rate	PAL :5MP@9x25fp,4MP@9x25fp,3MP@9x25fp, 1080P@9x25fp, 960P@9x25fp,720P@9x25fp, D1@9x25fp NTSC: 5MP@9x30fp,4MP@9x30fp, 3MP@9x30fp,1080P@9x30fp, 960P@9x30fp, 720P@9x30fp, D1@9x30fp
	Record Mode	Manual/Timer/Motion Detection

Playback & Backup	Local Sync Playback	1CH 5MP@30fps, 1CH 4Mp@30fps, 2CH 3M@30fps, 4CH 1080P@20fps, 4CH 960P@30fps, 4CH 720P@30fps
	Remote Sync Playback	YES
	Search Mode	ALL, Channel, Manual, Time, Date, Motion Detection, Event Alarm
	Playback Functions	Play, Pause, Stop, Rewind, Fast play, Slow Play, Full Screen, Frame Play, Frame Rewind, Digital Zoom
Network	Backup Mode	USB Device/Network
	Interface	5 x RJ45 10M/100M
	Incoming Bandwidth	60MB
	Outgoing Bandwidth	/
	Network Functions	TCP/IP, HTTP, UPnP, DNS, NTP, SMTP, PPPoE, DHCP, FTP, DDNS, RTP, RTSP, RTCP, p2p
	Onvif Version	Support Onvif 2.8
	Cloud Support (P2P)	Yes
	Smart Phone	iPhone, iPad, Android, Android Pad
	POE	8 port PoE 100Mbps, Support Plug and Play, Total Power Output ≤ 100W
	WIFI	/
Storage	Interface Type	1 SATA Hard Disk Interface (2.5"/3.5" SATA)
	Capacity	Up to 8TB capacity
	eSATA	/
General	Language	English, Vietnamese
	USB Interface	2 USB 2.0 Interfaces
	RS485	/
	Power Supply	52V DC/2500mA
	Working Environment	-10~55°C/ 10~90%
	Dimension (W×D×H)	260 x 215 x 43 mm
	Weight	2.0KG (without HDD)

