

F-SP3-16F2G-BL



KEY FEATURES

- 16 PoE Port 10/100Mbps POE port;
- 2 Uplink Port 100/1000Mbps
- Distance up to 250 m
- Support VLAN
- Support IEEE802.3AF/AT
- Each port max. power supply reached 30W

MODEL NO.ZZ	F-SP3-16F2G-BL
Product	16+2 port 250m POE switch(Built-in)
PoE Port	1 to 16 port support IEEE802.3af/at
UP link port	17 th -18 th port support 1000Mbps
PoE output	15.4W/30W IEEE802.3af/at
PoE whole power	≤250W
PoE type	End-span
Power distance	≤250m
Network Standard	IEEE 802.3, IEEE802.3u, 802.3x, 802.3af/at
Network Medium	100/1000BASE-TX: 5 class and above non shielded twisted pair
Data Distance	≤250m
Switch capability	12Gbps
Forwarding Mode	Store and forward
Forwarding Rate	100Mbps:14880pps
	1000Mbps:14800pps
	1000BASE-T: 1488095pps/port
MAC Address	2K MAC address table
Port function	Power priority mechanism, fast and forward MAC automatic learning and aging IEEE802.3X Full-duplex mode and backpressure for Half-duplex mode
Indicator	LINK/ACT. 100Mbps, POE Status indicator POWER indicator, EXTENDER indicator
Working Environment	Working Temperature: -10°C ~ 50°C
Input power	AC100 ~ 240V 50/60HZ
Weight	2.1kg
Size	270mm * 180mm * 44mm (L*W*H)

