

F-SP3-4F2F-BL



KEY FEATURES

- 4 PoE Port 10/100Mbps, 2 UpLink port 10/100Mbps
- Distance 250m
- Support IEEE802.3AF/AT

MODEL NO.ZZ	F-SP3-4F2F-BL
Product	4 Port POE Switch (Built-in)
POE Port	1 to 4 support IEEE802.3AF/AT Standard
Output Power	15.4W/30W IEEE802.3af/at
Power Pin	Both 1/2+, 3/6- and 4/5+, 7/8-
Whole Power	≤78W (52V 1.5A)
POE Protocol	IEEE 802.3af/IEEE 802.3at
POE Type	End-span
Power Distance	≤250m
Network Standard	IEEE 802.3, IEEE802.3u, 802.3x, 802.3af/at
Network Medium	10/100BASE-TX:5 class and above non shielded twisted pair
Data Distance	≤250m
Switch Capability	1.6Gbps
Forwarding Mode	Store and forward
Forwarding Rate	10BASE-T:14880PPS/port 100BASE-Tx : 14800pps/port
MAC Address	MAC address table 1K
Port Function	Power priority mechanism, fast and forward MAC automatic learning and aging IEEE802.3X Full-duplex mode and backpressure for Half-duplex mode
LED Indicator	LINK/ACT.100Mbps, PoE Status Indicator Power indicator, Extender
Working Environment	Working temperature : -10° ~ 55°C
Weight	1kg
Size	200mm * 120mm * 40mm(L*W*H)