

F-SP3-8F2F-BL



KEY FEATURES

- 8 PoE Port 10/100Mbps;
- 2 Uplink Port 10/100Mbps
- Distance up to 250m
- Support Vlan
- Support IEEE802.3AF/AT
- Each port max power supply reached 30W

MODEL NO.ZZ	F-SP3-8F2F-BL
Product	8+2 Port 250m POE Switch (Built-in)
POE Port	1 to 8 support IEEE802.3AF/AT Standard
Output Power	15.4W/30W IEEE802.3af/at
Power Pin	Both 1/2+, 3/6- and 4/5+, 7/8-
Whole Power	≤120W (52V 2.8A)
POE Protocol	IEEE 802.3af/IEEE 802.3at
POE Type	End-span
Power Distance	≤250m
Network Standard	IEEE 802.3, IEEE802.3u, 802.3x, 802.3af/at
Network Medium	10/100BASE-TX:5 class and above non shielded twisted pair
Data Distance	≤250m
Switch Capability	1.6Gbps
Forwarding Mode	Store and forward
Forwarding Rate	10BASE-T:14880PPS/port 100BASE-tx: 14800pps/port
MAC Address	MAC address table 2K
Port Function	Power priority mechanism, fast and forward MAC automatic learning and aging IEEE802.3X Full-duplex mode backpressure for Half-duplex mode
LED Indicator	LINK/ACT.100Mbps, PoE Status Indicator, Power indicator, Extender
Working Environment	Working temperature: -10° ~ 55°C
Weight	1.2kg
Size	200mm * 118mm * 44mm(L*W*H)

