

F-SP3-8F2G-BL



KEY FEATURES

- 8 PoE port 10/100Mbps;
- 2 port Uplink 100/1000Mbps
- Distance up to 250m
- Support Vlan
- Support IEEE802.3AF/AT
- Each port max. power supply reached 30W

MODEL NO.ZZ	F-SP3-8F2G-BL
Product	8+2 Port 250m PoE Switch (Built-in)
POE Port	1 to 8 support IEEE802.3AF/AT Standard
Output Power	15.4W/30W IEEE802.3af/at
Power Pin	1/2+, 3/6-
Whole Power	≤120W (52V 2.3A)
POE Protocol	IEEE 802.3af/IEEE 802.3at
POE Type	End-span
Power Distance	≤250m
Network Standard	IEEE 802.3, IEEE802.3u, 802.3x, 802.3af/at
Network Medium	10/100BASE-TX:5 class and above non shielded twisted pair
Data Distance	≤250m
Switch Capability	10Gbps
Forwarding Mode	Store and forward
Forwarding Rate	100Mbps:14880pps 1000Mbps:14800pps
MAC Address	MAC address table 2K
Port Function	Power priority mechanism, fast and forward MAC automatic learning and aging IEEE802.3X Full-duplex mode and backpressure for Half-duplex mode
LED Indicator	LINK/ACT.100Mbps, POE Status Indicator, Power indicator, Extender
Working Environment	Working temperature : -10° ~ 55°C
Weight	1.2kg
Size	270mm * 180mm * 44mm(L*W*H)

