

HU-ND223DMST/I3E



## KEY FEATURES

- Ultra 265, H.265, H.264
- IR: Up to 30m
- Support Starlight
- IP67
- IK10
- Built-in Mic
- Support Micro SD, up to 256GB
- Support PoE
- Smart Function: Motion detection, Tamper alarm, Cross line, Audio Detection, Intrusion detection, People counting

## Specification

	Model No.ZZ	HU-ND223DMST/I3E
Camera	Image Sensor	1/2.8" CMOS sensor
	Resolution	2Mp
	Minimum Illumination	Colour: 0.001Lux (F2.0, AGC ON), 0Lux with IR on
Lens	Focus length	2.8mm
	Lens Type	Fixed
	Shutter	Auto/Manual, 1 ~ 1/100000s
	View Angle	H: 106.7°, V: 57.1°, O: 115.7°
	DORI distance	D: 43.4m, O: 17.4m, R: 8.7m, I: 4.3m
Night vision	IR range	Up to 30m
	Wavelength	850nm
	IR On/Off Control	Auto/Manual
	Day/Night	IR-cut filter with auto switch (ICR)
Camera features	White Balance	Auto/Outdoor/Fine Tune/Sodium Lamp/Locked/Auto2
	DNR	2D/3D DNR
	S/N	>52dB
	WDR	120dB
	HLC	N/A
	BLC	Support
	Defog	Digital Defog
	9:16 Corridor Mode	Supported
	OSD	Up to 4 OSD
	Privacy Mask	Up to 4 areas
	ROI	Up to 8 areas
	Flip	Normal/Vertical/Horizontal/180°
	Motion detection	Up to 4 areas
Video	Video compression	Ultra 265, H.265, H.264, MJPEG
	H.264 code profile	Baseline profile, Main Profile, High Profile
	Frame rate	Main Stream: 2MP (1920*1080)/720P(1280*720)@30fps; Sub Stream: 720P (1280*720)/(720*576)/ 640*360@30fps; Third Stream: 720*576/ 640*360/ 704*288/ 352*288@30fps;
	Bit Rate	128 Kbps~6144 kbps
Audio	Built-in Mic	Support
	Compression	G.711
	Suppression	Support
	Sampling Rate	8kHz
	Audio I/O	1 Input: impedance 35kΩ; amplitude 2V [p-p] 1 Output: impedance 600Ω; amplitude 2V [p-p]

## Specification

<b>Smart Function</b>	Behavior Detection	Motion detection, Tamper alarm, Cross line, Audio Detection, Intrusion detection
	Statistical Analysis	People counting, support people flow counting and crowd density monitoring
<b>Network</b>	Protocols	IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, RTMP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, QoS, SSL, SNMP
	Onvif	ONVIF (Profile S, Profile G, Profile T), API
	Interface	10/100M Base-TX Ethernet
	Client	Hu-viewer Plus, Hu-VMS
	Web Browser	Plug-in required live view: IE9+, Chrome 41 and below, Firefox 52 and below
<b>General</b>	Storage	Micro SD, up to 256GB
	Power	DC 12V±25%, PoE(IEEE 802.3af) Max 6.0W
	Waterproof	IP67
	Vandal Resistant	IK10
	Surge Protection	4kV
	Material	Metal
	Working & Storage Environment	-30°C ~ 60°C (-22°F ~ 140°F), Humidity: ≤95% RH (non-condensing)
	Weight	0.37kg
	Dimensions	Φ110 x 61mm

## Dimensions

