

HU-ND822D/I3E



KEY FEATURES

- Ultra 265, H.265, H.264
- IR range: Up to 30m
- IP67
- Support PoE
- Smart Function: Human Body Detection, Motion Detection, Tampering Alarm

8MP

Ultra 265

day/night



IR 30m



IP67



Support



Smart

Specification

	Model No.ZZ	HU-ND822D/I3E
Camera	Image Sensor	1/2.9" CMOS sensor
	Resolution	8Mp
	Minimum Illumination	Colour: 0.02Lux (F2.0, AGC ON), 0Lux with IR on
Lens	Focus length	2.8mm
	Lens Type	Fixed
	View Angle	H: 97°, V: 57.5°, O: 126.1°
	DORI distance	D: 84m, O: 33.6m, R: 16.8m, I: 8.4m
Night vision	IR range	Up to 30m
Camera features	DNR	2D/3D DNR
	S/N	>56dB
	WDR	120dB
	HLC	Support
	BLC	Support
	Flip	Normal/Vertical/Horizontal/180°
	Privacy Mask	Up to 4 areas
	Motion detection	Up to 4 areas
Smart	Behavior Detection	Human Body Detection, Motion Detection, Tampering Alarm
Video	Video compression	Ultra 265, H.265, H.264, MJPEG
	H.264 code profile	Baseline profile, Main Profile
	Frame rate	Main Stream: 8MP(3072*2048) : Max. 20 fps; Sub Stream: 720P (1280*720) : Max. 20 fps; Third Stream: 4CIF (704*576) : Max. 20 fps
Network	Onvif	ONVIF (Profile S, Profile T), API
	Interface	10/100M Base-TX Ethernet
	Web Browser	Plug-in required live view: IE9+, Chrome 41 and below, Firefox 52 and below
General	Power	DC 12V±25%, PoE (IEEE 802.3af), Max 6W
	Waterproof	IP67
	Surge Protection	2kV
	Working Enviroment	-30°C ~ 60°C (-22°F ~ 140°F), Humidity: ≤95% RH (non-condensing)
	Weight	0.43kg
	Dimensions	Φ110.5 x 94.1mm (Φ 4.4" x 3.7")