

HU-NP225DMT/15E-AF



KEY FEATURES

- Ultra 265, H.265, H.264
- IR: Up to 50m
- IP67
- Built-in Mic
- Support Micro SD, up to 128GB
- Smart Function: Motion detection, Tampering Detection, Audio Detection, Human Body Detection
- Support PoE

Specification

	Model No.ZZ	HU-NP225DMT/I5E-AF
Camera	Image Sensor	1/2.7" CMOS sensor
	Resolution	2Mp
	Minimum Illumination	Colour: 0.005Lux (F1.6, AGC ON), 0Lux with IR on
Lens	Focus length	2.8~ 12mm
	Shutter	Auto/Manual, 1 ~ 1/100000s
	Lens Type	Auto focus
	View Angle	H: 108.05° ~ 32.59°, V: 56.81° ~ 18.36°, O: 111.91° ~ 36.53°
	DORI distance	D: 42 ~ 180m, O: 16.8 ~ 72m, R: 8.4 ~ 36 m, I: 4.2 ~ 18 m
Night vision	IR range	Up to 50m
	Wavelength	850nm
	Day/Night	IR-cut filter with auto switch (ICR)
	IR On/Off Control	Auto/Manual
Camera features	White Balance	Auto/Outdoor/Fine Tune/Sodium Lamp/Locked/Auto2
	DNR	2D/3D DNR
	WDR	120dB
	HLC	Support
	9:16 Corridor Mode	Supported
	BLC	Support
	Defog	Digital Defog
	OSD	Up to 4 OSD
	Privacy Mask	Up to 4 areas
	ROI	Up to 8 areas
	Flip	Normal/Vertical/Horizontal/180°
	Motion detection	Up to 4 areas
Smart Function	Behavior Detection	Motion detection, Tampering Detection, Audio Detection, Human Body Detection
Video	Video compression	Ultra 265, H.265, H.264, MJPEG
	H.264 code profile	Baseline profile, Main Profile, High Profile
	Frame rate	Main Stream: 1920*1080/ 1280*720@30fps Sub Stream: 1280*720/ 720*576/ 640*360/ 704*288/ 352*288@30fps;
	Video Bit Rate	128 Kbps~6144 kbps

Specification

Audio	Built-in Mic	Support
	Compression	G.711
	Suppression	Support
	Sampling Rate	8kHz
Network	Protocols	IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, RTMP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, QoS, SSL, SNMP
	Onvif	ONVIF (Profile S, Profile G, Profile T)
	Interface	1 RJ45 10/100M Base-TX Ethernet
	Client	Hu-viewer Plus, Hu-VMS(Hu-Cloud and Hu-DDNS free)
	Web Browser	Plug-in required live view: IE9+, Chrome 41 and below, Firefox 52 and below
General	Storage	Micro SD, up to 128GB
	Power	DC 12V±25%, PoE(IEEE 802.3af) Max 8.5W
	Waterproof	IP67
	Surge Protection	6kV
	Material	metal
	Working & Storage Enviroment	-30°C ~ 60°C (-22°F ~ 140°F), Humidity: ≤95% RH (non-condensing)
	Weight	0.54kg
	Dimensions	206 x 74 x 74mm

Dimensions

