

## HU-NP442DS/I5E



### KEY FEATURES

- Ultra 265, H.265, H.264
- IR range: Up to 50m
- IP67
- Support Starlight
- Support PoE
- Smart Function: Human Body Detection, Motion Detection, Tampering Alarm

## Specification

	<b>Model No.ZZ</b>	<b>HU-NP442DS/15E</b>
<b>Camera</b>	Image Sensor	1/3" CMOS sensor
	Resolution	4Mp
	Minimum Illumination	Colour: 0.005Lux (F1.6, AGC ON), 0Lux with IR on
<b>Lens</b>	Focus length	4.0mm
	Lens Type	Fixed
	View Angle	H: 79.7°, V: 41.6°, O: 98.0°
	DORI distance	D: 90m, O: 36m, R: 18m, I: 9m
<b>Night vision</b>	IR range	Up to 50m
<b>Camera features</b>	Starlight	Support
	DNR	2D/3D DNR
	S/N	>52dB
	WDR	120dB
	HLC	Support
	BLC	Support
	Defog	Digital Defog
	Privacy Mask	Up to 4 areas
	Motion detection	Up to 4 areas
<b>Smart</b>	Behavior Detection	Human Body Detection, Motion Detection, Tampering Alarm
<b>Video</b>	Video compression	Ultra 265, H.265, H.264, MJPEG
	H.264 code profile	Baseline profile, Main Profile, High Profile
	Frame rate	Main Stream: 4MP (2688*1520), Max 25fps; Sub Stream: 720P (1280*720), Max 25fps Third Stream: CIF (352*288), Max 25fps
<b>Network</b>	Web Browser	Plug-in required live view: IE9+, Chrome 41 and below, Firefox 52 and below
	Onvif	ONVIF (Profile S, Profile T), API
	Interface	10/100M Base-TX Ethernet
<b>General</b>	Power	DC 12V±25%, PoE (IEEE 802.3af), Max 6W
	Waterproof	IP67
	Working Enviroment	-30°C ~ 60°C (-22°F ~ 140°F), Humidity: ≤95% RH (non-condensing)
	Weight	0.5kg
	Dimensions	191.3×72.6×70.9mm (7.5"×2.9"×2.8")