

## HU-NP525DMT/I5E-AF



### KEY FEATURES

- Ultra 265, H.265, H.264
- IR: Up to 50m
- IP67
- Built-in Mic
- Support Micro SD, up to 256GB
- Support PoE
- Smart Function: Motion detection, Tamper alarm, Cross line, Audio Detection, Intrusion detection(based on human body detection)

## Specification

	Model No.ZZ	HU-NP525DMT-I5E-AF
Camera	Image Sensor	1/2.7" CMOS sensor
	Resolution	5Mp
	Minimum Illumination	Colour: 0.003Lux (F2.0, AGC ON), 0Lux with IR on
Lens	Focus length	2.8~12mm
	Lens Type	Auto focus, Motorized zoom lens
	Shutter	Auto/Manual, 1 ~ 1/100000s
	View Angle	H: 108.79°~ 33.23°, V: 56.90°~ 18.33°, O: 112.56°~37.46°
	DORI distance	D: 63.0~270.0m, O: 25.2~108.0m, R: 12.6~54.0m, I: 6.3~27.0m
Night vision	IR range	Up to 50m
	Wavelength	850nm
	IR On/Off Control	Auto/Manual
	Day/Night	IR-cut filter with auto switch (ICR)
Camera features	Starlight	Support
	White Balance	Auto/Outdoor/Fine Tune/Sodium Lamp/Locked/Auto2
	DNR	2D/3D DNR
	S/N	>56dB
	WDR	120dB
	HLC	Support
	BLC	Support
	Defog	Digital Defog
	OSD	Up to 4 OSD
	Privacy Mask	Up to 4 areas
	ROI	Up to 8 areas
	Flip	Normal/Vertical/Horizontal/180°
Video	Video compression	Ultra 265, H.265, H.264, MJPEG
	H.264 code profile	Baseline profile, Main Profile, High Profile
	Frame rate	Main Stream: 5MP (2880*1620)/ 4MP (2560*1440), Max 25fps; 3MP (2304*1296)/ 1080P (1920*1080), Max 30fps; Sub Stream: 1280*720/ 720*576/ 640*360,Max 30fps;
	Bit Rate	128 Kbps~16Mbps
	Audio	Built-in Mic
Compression		G.711U, G.711A
Suppression		Support
Sampling Rate		8kHz

## Specification

<b>Smart Function</b>	Behavior Detection	Motion detection, Tamper alarm, Cross line, Audio Detection, Intrusion detection(Based on human body detection)
<b>Network</b>	Protocols	IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, RTMP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, QoS, SSL, SNMP
	Onvif	ONVIF (Profile S, Profile G, Profile T), API
	Interface	10/100M Base-TX Ethernet
	Client	Hu-viewer Plus, Hu-VMS
	Web Browser	Plug-in required live view: IE9+, Chrome 41 and below, Firefox 52 and below
<b>General</b>	Storage	Micro SD, up to 256GB
	Power	DC 12V±25%, PoE(IEEE 802.3af) Max 8.5W
	Waterproof	IP67
	Surge Protection	6kV
	Material	Metal
	Working & Storage Environment	-30°C ~ 60°C (-22°F ~ 140°F), Humidity: ≤95% RH (non-condensing)
	Weight	0.55kg
	Dimensions	206 × 74 × 74mm

## Dimensions

