

HU-NP822DST/I10E-AF



KEY FEATURES

- Ultra 265, H.265, H.264
- IR: Up to 100m
- IP67
- IK10
- Support Micro SD, up to 256GB
- Smart Function: Motion detection, Tampering Detection, Audio Detection, Intrusion detection, People counting, Object Left Behind detection, Object Removed detection, Defocus detection, Scene change detection
- Support PoE

Specification

	Model No.ZZ	HU-NP822DST/I10E-AF
Camera	Image Sensor	1/1.8" CMOS sensor
	Resolution	8Mp
	Minimum Illumination	Colour: 0.002Lux (F1.2, AGC ON), 0Lux with IR on
Lens	Focus length	2.8~ 12mm
	Shutter	Auto/Manual, 1 ~ 1/100000s
	Lens Type	Auto focus, Motorized zoom lens
	View Angle	H: 41.6°~106.5°, V: 24.0°~55.0°, D: 47°~126°
	DORI distance	D: 63.0~270.0m, O: 25.2~108.0m, R: 12.6~54m, I: 6.3~27m
Night vision	IR range	Up to 100m
	Wavelength	850nm
	Day/Night	IR-cut filter with auto switch (ICR)
	IR On/Off Control	Auto/Manual
Camera features	White Balance	Auto/Outdoor/Fine Tune/Sodium Lamp/Locked/Auto2
	DNR	2D/3D DNR
	WDR	120dB
	HLC	Support
	9:16 Corridor Mode	Supported
	BLC	Support
	Defog	Digital Defog
	OSD	Up to 4 OSD
	Privacy Mask	Up to 4 areas
	ROI	Up to 8 areas
	Flip	Normal/Vertical/Horizontal/180°
Motion detection	Up to 4 areas	
Smart Function	Behavior Detection	Motion detection, Tampering Detection, Audio Detection, Cross line detection, Intrusion detection, People counting, Object Left Behind detection, Object Removed detection, Defocus detection, Scene change detection
Video	Video compression	Ultra 265, H.265, H.264, MJPEG
	Frame rate	Main Stream: 8MP(3840*2160), 4MP(2560*1440), 2MP(1920*1080), Max 30fps; Sub Stream: 2MP (1920*1080), Max 30fps; Third Stream: D1 (720*576), Max 30fps Fourth Stream: D1 (720*576), Max 30fps Fifth Stream: D1 (720*576), Max 30fps
	Video Bit Rate	128 Kbps~ 16Mbps

Specification

Audio	Two-way Audio	Support(Connect external speaker and microphone)
	Compression	G.711U, G.711A
	Suppression	Support
	Sampling Rate	8kHz
Interface	Audio I/O	1/1
	Alarm I/O	2/1
Network	Protocols	IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, RTMP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, QoS, SSL, SNMP
	Onvif	ONVIF (Profile S, Profile G, Profile T)
	Interface	1 x RJ45 10M/100M/1000M Base-TX Ethernet
	Client	Hu-viewer Plus, Hu-VMS(Hu-Cloud and Hu-DDNS free)
	Web Browser	Plug-in required live view: IE9+, Chrome 41 and below, Firefox 52 and below
General	Storage	Micro SD, up to 256GB
	Power	AC24V±25%, DC12V(-10%~+25%), PoE(IEEE802.3at), Max 14W
	Waterproof	IP67
	Vandal Resistant	IK10
	Surge Protection	6kV
	Material	metal
	Working & Storage Enviroment	-40°C ~60°C (-40°F ~ 140°F), Humidity: ≤95% RH (non-condensing)
	Weight	1.60kg
	Dimensions	Φ306.4x104.1x98.1mm

Dimensions

