

HU-RN1008M



KEY FEATURES

- 10 Chanel input
- Ultra 265, H.265, H.264
- Up to 2Mp resolution recording
- Third-party IP camera with ONVIF
- 1 SATA HDD, up to 6TB
- Support cloud upgrade

Specification

Model	HU-RN1008M	
Video/Audio Input	IP video input	8/10ch
Video/Audio Output	HDMI/VGA output	HDMI: 1920x1080p/ 1600x1200/ 1280x1024/ 1280x720/1024x768 VGA: 1920x1080p/ 1600x1200/ 1280x1024/1280x720/1024x768
	Recording resolution	1080p/960p/720p/D1/2CIF/CIF
	Synchronous playback	4ch
	Corridor mode screen	3/4/5/7/9
Network	Network interface	1 RJ45 10/100M- Ethernet
	Incoming Bandwidth	40Mbps
	Output Bandwidth	40Mbps
	Remote users	128
	Client	HU-Viewer, HU-VMS
Decoding	Video compression	Ultra 265/H.265/H.264
	Live view/Playback	1080p/960p/720p/D1/2CIF/CIF
	Capability	2 x 1080p@30fps, 4 x 720p@30fps
Storage	Interface Type	1 SATA
	Capacity	Up to 6TB
External Interface	USB interface	2 USB2.0
General	Power Supply	12V DC Power Consumption: ≤3.2 W(without HDD)
	Working enviromnet	-10°C ~ + 55°C (+14°F ~ +131°F) Humidity ≤ 90% RH(non-condensing)
	Dimension(WxDxH)	260mm × 240mm × 46mm(10.2" × 9.4" × 1.8")
	Weight(without HDD)	0.9kg

Drawing

