

HU-RN1216M



KEY FEATURES

- 16 Chanel input
- Up to 4K resolution recording
- Ultra 265, H.265, H.264
- 1 SATA HDD, up to 6TB
- Support cloud upgrade

Specification

	Model	HU-RN1216M
Video/Audio Input	IP video input	16ch
Video/Audio Output	HDMI/VGA output	HDMI: 3840x2160/30Hz, 1920x1080p/60Hz, 1920x1080p/50Hz, 1600x1200/60Hz, 1280x1024/60Hz, 1280x720/60Hz, 1024x768/60Hz VGA: 1920x1080p/60Hz, 1920x1080p/50Hz, 1600x1200/60Hz, 1280x1024/60Hz, 1280x720/60Hz, 1024x768/60Hz
	Two-way Audio output	1ch, RCA
	Recording resolution	4K/5MP/4MP/3MP/1080p/960p/720p/D1/2CIF/CIF
	Synchronous playback	16ch
	Corridor mode screen	3/4/5/7/9/10/12/16
Network	Network interface	1 RJ45 10/100M- Ethernet
	Incoming Bandwidth	64Mbps
	Output Bandwidth	64Mbps
	Remote users	128
	Client	HU-Viewer, HU-VMS
Decoding	Video compression	Ultra 265/H.265/H.264
	Live view/Playback	4K/5MP/4MP/3MP/1080p/960p/720p/D1/2CIF/CIF
	Capability	2 x 4K@30, 3 x 5MP@30, 4 x 4MP@30, 5 x 3MP@30, 8 x 1080p@30, 16 x 720p@30
Storage	Interface Type	1 SATA
	Capacity	Up to 6TB
External Interface	USB interface	1 USB2.0, 1 USB3.0
General	Power Supply	12V DC, Max 8W(without HDD)
	Working enviromnet	-10°C ~ + 55°C (+14°F ~ +131°F), Humidity ≤ 90% RH(non-condensing)
	Dimension(WxDxH)	260mm × 240mm × 47mm (10.2"×9.4"×1.9")
	Weight(without HDD)	1.3kg

Drawing

