

## HU-RN2216M



### KEY FEATURES

- 16 Chanel input
- Up to 8Mp resolution recording
- Ultra 265, H.265, H.264
- 2 SATA HDD, up to 6TB for each HDD
- Support cloud upgrade
- Smart Function: Face detection, Intrusion detection, Cross line detection, Audio detection, Defocus detection, Scene change detection, Auto tracking, Face search, Behavior search, People counting

## Specification

	Model	HU-RN2216M
<b>Video/Audio Input</b>	IP video input	16ch
<b>Video/Audio Output</b>	HDMI/VGA output	HDMI: 3840x2160/ 1920x1080p/ 1600x1200 1280x1024/ 1280x720/ 1024x768 VGA: 1920x1080p/ 1280x1024/ 1280x720/ 1024x768
	Two-way Audio output	1ch, RCA
	Recording resolution	8MP/6MP/5MP/4MP/3MP/1080p/960p/720p/D1/2CIF/CIF
	Synchronous playback	16ch
	Corridor mode screen	3/4/5/7/9/10/12/16
<b>Network</b>	Network interface	1 RJ45 10/100M- Ethernet
	Incoming Bandwidth	160Mbps
	Output Bandwidth	64Mbps
	Remote users	128
	Client	HU-Viewer, HU-VMS
<b>Decoding</b>	Video compression	Ultra 265/H.265/H.264
	Live view/Playback	8MP/6MP/5MP/4MP/3MP/1080p/960p/720p/D1/2CIF/CIF
	Capability	2CH x 4K@30fps, 3CHx 5MP@30fps, 4CHx4MP@30fps, 5CH x 3MP@30, 8CH x 1080p@30fps, 16CH x 720p@30fps
<b>Storage</b>	Interface Type	2 SATA
	Capacity	Up to 8TB for each disk
<b>Smart</b>	VCA Detection	Face detection, Intrusion detection, Cross line detection, Audio detection, Defocus detection, Scene change detection, Auto tracking
	VCA Search	Face search, Behavior search
	Statistical Analysis	People counting
<b>External Interface</b>	USB interface	2 USB2.0, 1 USB3.0
<b>General</b>	Power Supply	12V DC, Max 15W( without HDD )
	Working enviromnet	-10°C ~ + 55°C ( +14°F ~ +131°F ) Humidity ≤ 90% RH(non-condensing)
	Dimension(WxDxH)	380mm × 315mm ×53mm (15.0" × 12.4" ×2.1" )
	Weight(without HDD)	0.98kg