

## HU-RN4232M



### KEY FEATURES

- 32 Chanel input
- Up to 8Mp resolution recording
- Ultra 265, H.265, H.264
- 4 SATA HDD, up to 6TB for each HDD
- Support cloud upgrade

## Specification

	Model	HU-RN4232M
Video/Audio Input	IP video input	32ch
	Two-way Audio Input	1-ch, RCA
Video/Audio Output	HDMI/VGA output	HDMI: 4K (3840x2160)/1920x1080p/1600x1200 1280x1024/1280x720/1024x768 VGA: 1920x1080p/1280x1024/1280x720/1024x768
	Two-way Audio output	1ch, RCA
	Recording resolution	8MP/5MP/4MP/3MP/1080p/960p/720p/960H/D1/2CIF/CIF
	Synchronous playback	32ch
	Corridor mode screen	3/4/5/7/9/10/12/16/32
Network	Network interface	2 RJ-45 10/100/1000M Ethernet
	Incoming Bandwidth	160Mbps
	Output Bandwidth	64Mbps
	Remote users	128
	Client	HU-Viewer, HU-VMS
Decoding	Video compression	Ultra 265/H.265/H.264
	Live view/Playback	8MP/5MP/4MP/3MP/1080p/960p/720p/D1/2CIF/CIF
	Capability	2CH x 4K@30fps, 3CH x 5MP@30fps, 4CH x 4MP@30fps, 5CH x 3MP@30fps, 8CH x 1080p@30fps, 16CH x 720p@30fps, 32CH x D1
Storage	Interface Type	4 SATA
	Capacity	Up to 6TB for each disk
External Interface	USB interface	2 USB 2.0, 1 USB 3.0
General	Power Supply	12V DC, Max 15W( without HDD )
	Working enviromnet	-10°C ~ + 55°C ( +14°F ~ +131°F ), Humidity ≤ 90% RH(non-condensing)
	Dimension(WxDxH)	440mm × 344mm ×50mm (17.3" × 13.5" ×2.0")
	Weight(without HDD)	3.15kg

## Drawing

