

HU-RNR162128M



KEY FEATURES

- 128 Chanel input
- Up to 12Mp resolution recording
- Support 2 HDMI, 1 VGA
- HDMI1 & HDMI2 up to 4K resolution
- HDMI1, HDMI2, VGA independent output provided
- Ultra 265, H.265, H.264
- 16 SATA HDD, up to 10TB for each HDD
- Support RAID 0, 1, 5, 6, 10, 50, 60
- Support Hu-DDNS

Specification

	Model	HU-RNR162128M
Video/Audio Input	IP video input	128ch
	Two-way Audio Input	1-ch, BNC
Video/Audio Output	HDMI/VGA output	HDMI1/HDMI2: 4K (3840x2160)/, 1920x1080p/1600x1200/1280x1024/1280x720/1024x768 VGA: 1920x1080p/1600x1200/1280x1024/1280x720/1024x768
	Audio output	1ch, BNC
	Recording resolution	12MP/8MP/6MP/5MP/4MP/3MP/1080p/960p/720p/D1/2CIF/CIF
	Synchronous playback	16ch
	Corridor mode screen	3/4/5/7/9/10/12/16/32
Network	Network interface	4 RJ-45 10M/100M/1000M adaptive Ethernet Interface 2 1000M SFP Ethernet Interface
	Protocols	P2P, UPnP, NTP, DHCP, PPPoE
	DDNS	Support Hu-DDNS
	Onvif	Profile S, Profile G, Profile T
	Incoming Bandwidth	384Mbps
	Output Bandwidth	384Mbps
	Remote users	128
	Client	HU-Viewer, HU-VMS
Decoding	Video compression	Ultra 265/H.265/H.264
	Live view/Playback	12MP/8MP/6MP/5MP/4MP/3MP/1080p/960p/720p/D1/2CIF/CIF
	Capability	4 x 12MP@20fps, 4 x 4K@30fps, 16 x 1080p@30fps, 36 x 720p@30fps, 64 x D1
Storage	Interface Type	16 SATA, 1 eSATA interface, 2 miniSAS ports
	Capacity	Up to 10TB for each disk
	Array Type	RAID 0/1/5/6/10/50/60
External Interface	USB interface	Rear panel 4 USB 3.0
	Alarm In/Out	24 input, 8 output
	Decoding Card (optional)	2 slots (4-ch HDMI or 6-ch HDMI outputs per card)
	Serial Interface	1 RS232, 1 RS485
	Power Output	12V

Specification

General	Power Supply	100~240VAC, Max 50W(without HDD)
	Working enviromnet	-10°C ~ + 55°C (+14°F ~ +131°F), Humidity ≤ 90% RH(non-condensing)
	Chassis	19-inch rack-mounted 3U chassis
	Dimension(WxDxH)	482mm ×477mm ×131mm (18.8" × 19"×5.1")
	Weight(without HDD)	<10kg

Dimensions

