

### ▶ KEY FEATURES



- 32 Chanel input
- Up to 12Mp resolution recording
- Support 2 HDMI, 1 VGA
- HDMI1 & HDMI2 up to 4K resolution
- HDMI1, HDMI2, VGA independent output provided
- Ultra 265, H.265, H.264
- 8 SATA HDD, up to 10TB for each HDD
- Support RAID 0, 1, 5, 6, 10



### ► SPECIFICATION

	Model	HU-RNR8232M
Video/Audio Input	IP video input	32ch
	Two-way Audio Input	1-ch, RCA
Video/Audio Output	HDMI/VGA output	HDMI1/HDMI2(HDMI audio output is not supported): 4K (3840x2160)/, 1920x1080p/1600x1200/1280x1024/1280x720/1024x768 VGA: 1920x1080p/1600x1200/1280x1024/1280x720/1024x768
	Audio output	1ch, RCA
	Recording resolution	12MP/8MP/6MP/5MP/4MP/3MP/1080p/960p/720p/D1/2CIF/CIF
	Synchronous playback	16ch
	Corridor mode screen	3/4/5/7/9/10/12/16/32
Network	Network interface	2 RJ45 10/100M/1000M- Ethernet
	Onvif	Profile S, Profile G, Profile T
	Protocols	P2P, UPnP, NTP, DHCP, PPPoE
	Incoming Bandwidth	384Mbps
	Output Bandwidth	384Mbps
	Remote users	128
	Client	HU-Viewer, HU-VMS
Decoding	Video compression	Ultra 265/H.265/H.264
	Live view/Playback	12MP/8MP/6MP/5MP/4MP/3MP/1080p/960p/720p/D1/2CIF/CIF
	Capability	2CH x 12MP@30fps, 4CH x 4K@30fps, 8CH x 4MP@30fps, 9CH x 4MP@25fps 16CH x 1080P@30fps, 32CH x 960P@25fps
Storage	Interface Type	8 SATA, 1 eSATA interface
	Capacity	Up to 10TB for each disk
	Array Type	RAID 0, 1, 5, 6, 10
External Interface	USB interface	2 USB 2.0, 1 USB 3.0
	Alarm In/Out	16 input, 4 output
	Serial Interface	1 RS232, 1 RS485
General	Power Supply	100~240VAC, Max 25W( without HDD )
	Working enviromnet	-10°C ~ + 55°C ( +14°F ~ +131°F ), Humidity ≤ 90% RH(non-condensing)
	Dimension(WxDxH)	442mm x426mm x89mm (17.4" x 16.8"x3.5")
	Weight(without HDD)	5.7kg