

HU-RN2216M



KEY FEATURES

- 16 Chanel input
- Up to 12Mp resolution recording
- Ultra 265, H.265, H.264
- 2 SATA HDD, up to 8TB for each HDD
- Built-in alarm input, ouput terminal
- Smart Function: Face detection, Intrusion detection, Cross line detection, Audio detection, Defocus detection, Scene change detection, Auto tracking, Face search, Behavior search, People counting

Specification

	Model	HU-RN2216M
Video/Audio Input	IP video input	16ch
	Two-way Audio Input	1-ch, RCA
Video/Audio Output	HDMI/VGA output	HDMI: 3840x2160/ 1920x1080p/ 1600x1200 1280x1024/ 1280x720/ 1024x768 VGA: 1920x1080p/ 1280x1024/ 1280x720/ 1024x768
	Two-way Audio output	1ch, RCA
	Recording resolution	12MP/8MP/6MP/5MP/4MP/3MP/1080p/960p/720p/D1/2CIF/CIF
	Synchronous playback	16ch
	Live View Display	1/4/6/8/9/16
	Corridor mode screen	3/4/5/7/9/10/12/16
Network	Protocols	TCP/IP, P2P, UPnP, NTP, DHCP, PPPoE, HTTP, TTPS, DNS, DDNS, SNMP, SMTP, NFS
	Network interface	2 RJ45 10/100/1000M- Ethernet
	Incoming Bandwidth	320Mbps
	Output Bandwidth	320Mbps
	Remote users	128
	Client	HU-Viewer, HU-VMS
Decoding	Video compression	Ultra 265/H.265/H.264
	Live view/Playback	12MP/8MP/6MP/5MP/4MP/3MP/1080p/960p/720p/D1/2CIF/CIF
	Capability	1CH x 12MP@30fps, 2CH x 4K@30fps 5CH x 4MP@30fps, 10CH x 1080P@30fps, 16CH x 720P@30fps
Storage	Interface Type	2 SATA
	Capacity	Up to 8TB for each disk
Event alarm	General Alarm	Motion, Tampering, Human Body Detection, Video Loss, Input Alarm, Audio Detection
	Alert Alarm	IP Conflict, Network Disconnected, Disk Offline , Disk Abnormal, Illegal Access, Hard Disk Space Low, Hard Disk Full, Recording/Snapshot Abnormal

Specification

Smart	VCA Detection	Intrusion Detection, Cross Line Detection, Enter Area, Leave Area, Defocus Detection, Scene Change Detection, Object Left Behind, Object Removed, Auto Tracking
	VCA Search	Behavior search, Vehicle Search
	Statistical Analysis	People flow counting, Crow density Monitoring
External Interface	Alarm In	8-ch
	Alarm Out	2-ch
	RS485	1
	USB interface	2 USB2.0, 1 USB3.0
General	Power Supply	12V DC/ 3.3A Max 12W(without HDD)
	Working enviromnet	-10°C ~ + 55°C (+14°F ~ +131°F) Humidity ≤ 90% RH(non-condensing)
	Dimension(WxDxH)	380mm × 315mm ×53mm (15.0" × 12.4" ×2.1")
	Weight(without HDD)	1.8kg